

5200QL

QUICK-LOAD CORDLESS RIDE-ON SCRAPER



Features

The 5200QL is designed for jobs that require continuous operation, and it offers the only slide-out replaceable battery in the industry with a rear-accessed battery pack that is easily installed, changed, and transported. With no belts or gears, this scraper boasts low maintenance costs while maximizing production. Great for commercial surface removal and preparation, it is quiet and compact enough for residential jobs.

- A. Automatic kill switch is triggered when the operator seat is vacant
- B. Control levers with forward, reverse, and automatic return to neutral
- C. Ergonomic design includes movable foot pegs and an adjustable seat that allows for optimal operator comfort and the best possible line of sight
- D. Quick-change swivel head
- E. Extra weight compartments
- F. Larger/deepened forklift pockets
- G. Nonmarking tires
- H. E-stop knob for safety
- I. Trailer hitch
- J. Flip-up back lid for quick and easy battery changing
- K. New front debris deflector protects machine from loose material
- L. Front caster wheels allow increased maneuverability in tight spaces

Included with the 5200QL

- 7050-6: 6-inch cutting head
- 7050-12: 12-inch cutting head
- 6277: 12-inch .094 bevel up self-scoring blade
- 6284: 12-inch .094 heavy-duty blade
- 6285: 6-inch .094 heavy-duty blade
- 6286: 10-inch .094 heavy-duty blade
- 5110-404: Weight, 75 pounds (1) (rear)
- 5110-100: Front-wheel assembly
- 74854: Weight, 37 pounds (10) (front)
- 6254: 50-foot, 12-gauge extension cord (2)
- 5200QL-500: Two transport carts - 5200QL only
- 5204: Power Pack (one pack on the machine and one additional)
- 5212: 48-volt battery charger
- 7079-2: 2-inch angle shank with carbide tip
- 70549: Wrench
- Instruction manual
- One-year manufacturer's warranty on parts and labor

5200QL Specifications

Width*	24.75"	63 cm
Height	46.5"	119 cm
Length*	57"	145 cm
Weight	1,760 lb	798.3 kg
Removable Weight	370 lb front, 75 lb rear	167.8 kg front, 34 kg rear
Weight (machine only)	1,315 lb	596.5 kg
Speed	up to 120 ft/min	up to 36.6 m/min
Voltage	115	
Frequency	60 Hz	

*Measurements are without tooling attached.

THIS IS A SPECIAL ORDER MACHINE. Please contact your territory manager or our customer service department for more information and lead times.