

ENDURABLE

POWER STRIPPER™



- Product contains no toxic solvents
- Product contains no caustics
- Works on almost any sealer, coating, varnish, or paint
- Long-lasting as evaporation rate is much slower than typical solvent-based strippers, allowing product to remove several layers of coatings without losing strength
- Easy to apply by roller or mop
- It will not burn skin
- Mild odor allows for indoor applications
- Clean-up is easy
- Works over most substrates (not recommended over resilient surfaces such as vinyl, vct, or rubber)
- Good coverage rates make product very cost-effective

COVERAGE RATES: 75-200 square feet per gallon depending coating to be removed and how many layers of coating.

PACKAGING: Available in 1 gallon jug and 5 gallon bucket.

SHELF LIFE AND STORAGE: Product has an unlimited shelf life when left unopened in original containers. Keep product free from excessive heat. Product should be applied at temperatures above 45 degrees or product may not be fully effective.

WHERE TO USE: Use on any horizontal substrate other than resilient surfaces, such as vinyl, vct, or rubber.

APPLICATION INSTRUCTIONS: We highly recommend doing a small test area to determine effectiveness, coverage rate, and time needed for product to work.

1. Properly mask off areas with polyethylene sheeting and tape before applying product.
2. Completely wet the surface with ENDURABLE POWER STRIPPER. The best way to apply the stripper is with a mop or a roller. You may use a brush, or other type of applicator, but mop or roller is the easiest for large areas.
3. Allow time for stripper to work. The coating needs to be completely softened before removal, so allowing the stripper to complete its job is very important. This can take several hours. Covering the material with polyethylene sheeting is an option for keeping the material wet and working, especially in hot conditions. As long as the material is shiny and wet, it is still absorbing and working on the coating. If the material is not shiny, it may require more stripper. **DO NOT LET PRODUCT DRY OR YOU MAY HAVE TO REPEAT THE PROCESS. THE COATING MAY RECONSTITUTE IF IT DRIES.**
4. Test the coating to determine if the product is ready for removal. Scratch a small area. If the coating comes up easily, it is ready for removal. If not, let the product continue to work. In some cases the stripper will make the coating goopy and if this occurs, continue to apply more material and agitate the coating until the product liquefies.
5. Removal of the coating can be performed with scrapers, high-pressure water, or a low-speed buffer with strip pads or brushes. After the coating is completely removed, clean the surface with soap and water. The slurry can be removed with a wet-vac.

LIMITATIONS: Product should be applied at temperatures above 45 degrees Fahrenheit. You should not walk on the stripper with rubber or vinyl soled shoes as the stripper softens rubber and vinyl.

PRODUCT AVAILABILITY: Product is available at retail distributors around the world. Go to www.endurableproducts.com to find the nearest distributor.

DISPOSAL: Product is safe, biodegradable, and environmentally friendly. However, if the coating that is being removed is hazardous, check with local, state, and federal regulations for proper disposal.

WARNINGS: Use with proper ventilation. May cause eye and skin irritation. If you experience headaches, dizziness, or watery eyes, you may wear a NIOSH TC-84 respirator during application.

WARRANTY: Evaluate whether this product is suitable for your intended application. Conditions of product use are outside of our control and vary widely. The following is made in lieu of all express or implied warranties of merchantability. Our only obligation and your only remedy is replacement of product, at the option of HDIP INC. In no case will HDIP INC be liable for any direct, indirect, special, incidental, or consequential damages including lost profits, goodwill, or business opportunity.

"I removed the paint with POWER STRIPPER and brought the patio back to its original glory. This job would not have been possible without ENDURABLE POWER STRIPPER. Thank you!"
ROGER MCCLURE
PACIFIC STONESCAPES

BEFORE



AFTER



All products are labeled with full instructions. Additional information may be found on technical data sheets available at our website: www.endurableproducts.com. You may also view helpful instructional videos available on the website.

ENDURABLE

CONCRETE PRODUCTS™

The website provides additional tips and techniques for the individual products. Color selections are also available on website.

www.endurableproducts.com

800-910-3120