



## T20 Specifications | Industrial Rider Scrubber

### SCRUBBING SYSTEM

Cleaning path	
Cylindrical main brushes	40 in   1,020 mm
Disk main brushes	42 in   1,070 mm
With scrubbing side brush	54 in   1,370 mm
With sweeping side brush (cylindrical only)	56 in   1,420 mm
Cylindrical main brushes	
Brush speed	480 rpm
Brush diameter (2)	12 in   300 mm
Brush down pressure (up to)	390 lb   177 kg
Disk main brushes	
Brush speed	230 rpm
Brush diameter (3)	14 in   360 mm
Brush down pressure (up to)	400 lb   181 kg
Disk side brush	
Brush speed	150 rpm
Brush diameter – scrubbing	16 in   410 mm
Brush diameter – sweeping (cylindrical only)	21 in   533 mm
Tanks	
Solution tank	80 gal   303 L
Solution capacity with ES <sup>®</sup>	125 gal   473 L
Recovery tank	95 gal   360 L
Demisting chamber	15 gal   57 L
Debris tray (cylindrical only)	
Volume capacity	1.1 ft <sup>3</sup>   31 L
Weight capacity	110 lb   50 kg
Vacuum fan	
Speed	11,000 rpm
Water lift	35 in   890 mm

### PROPELLING SYSTEM

Propel speed forward (variable up to)	8.0 mph   12.9 km/h
Propel speed reverse (variable up to)	3.0 mph   4.8 km/h
Engine-gasoline/LPG (2.0 L)	
Gross Intermittent Power*	60.0 hp / 44.7 kW @3000 rpm
Tennant Governed Power	50.0 hp / 37.3 kW @2300 rpm
Moteur Diesel (1.5 L)	
Gross Intermittent Power*	24.8 hp / 18.5 kW @2300 rpm
Tennant Governed Power	24.8 hp / 18.5 kW @2300 rpm
Gradeability	
Transport at gross weight	10.0 deg / 18.0%
Working (cleaning)	8.0 deg / 14.0%
Ground clearance (transport)	
	3 in   80 mm
Tire front (1), solid	18 x 5.5 in   460 x 140 mm
Tires rear (2), solid	16 x 3.5 in   410 x 90 mm

### MACHINE DIMENSIONS

Length	95 in   2,410 mm
Width	
Frame	50 in   1,270 mm
Rear squeegee	51 in   1,300 mm
With side brush	58 in   1,473 mm
Height	
With overhead guard	83.5 in   2,120 mm
Weight	
Empty	3,300 lb   1,497 kg
GVW	4,900 lb   2,223 kg
Minimum aisle turn	110 in   2,790 mm

### STANDARD FEATURES

- 1-Step™ one button scrub operation
- Touch-n-Go™ wheel-mounted module
- Wheel-mounted horn
- Wheel-mounted water shut-off
- No-tool squeegee change
- No-tool brush change
- Yellow maintenance touch points
- Demisting chamber
- Dura-Track™ parabolic squeegee
- Cushion rollers
- Fire extinguisher
- SmartRelease™ breakaway squeegee system
- Headlights and LED taillights w/ back-up alert
- High-density Duramer™ exterior
- MaxPro<sup>2</sup>™ hydraulic technology
- Underwriter's Laboratory (UL) certified

### OPTIONAL EQUIPMENT

- Pro-Panel™ controls
- ec-H2O™ solution system
- ES<sup>®</sup> Extended Scrub w/detergent metering
- AV backup alarm (LED)
- Fire extinguisher
- Flashing warning light
- Overhead guard
- Vacuum wand (wet pick-up)
- Safety warning light
- Side Brush - Edge cleaning for scrubbing or sweeping
- Spray hose – 15 ft / 5 m w/ cleanout tool
- Squeegee protection kit
- Squeegee vacuum wand
- Strobing warning light
- Pressure washer (2200 psi) with 25 ft (7.0 m) hose
- IRIS<sup>®</sup> solution\*\*
- Underwriters Laboratory (UL<sup>®</sup>) Type LPS Certified

### WARRANTY

Please refer to your local Tennant representative for information.

For a complete selection of genuine Tennant brushes and pads, please consult the *T20 Parts and Consumables Reference Guide*.

\*Per SAE J1995

\*\*Available in select regions