

Category > Strengthen

## Eco-Hard MS

### Mono Silicate Densifier

### Product Description

Ameripolish® Eco-Hard MS Mono-silicate Densifier improves surface performance and resists the harmful effects of traffic wear and weathering. Ameripolish® Eco-Hard MS dust proofs, hardens, and cures the targeted surface in order to protect against dusting, pitting, spalling, and efflorescence that can be seen on untreated concrete. Ameripolish® Eco-Hard MS is odorless, colorless, and non-toxic.

### Features

- Ideal for new construction, existing concrete, and burnishing-only specs
- Minimizes dust for healthier indoor air quality
- Odorless, non-flammable, VOC Compliant
- Helps reduce efflorescence and alkali silica reaction (ASR)
- Less than 40% Solids

### Uses

Ameripolish® Eco-Hard MS can be used by itself or with Ameripolish® dyes and stain protectors.

- Harden concrete surfaces
- Prepares surface for high gloss diamond polishing
- Locks in dyes for longer lasting color
- Dust proofs, hardens, and cures surface

### Dilution & Coverage

Ameripolish® Eco-Hard MS is a Ready to Use (RTU) product and should not be mixed with any other product.

### Application (Polished Concrete Method)

For Preparation:

Sweep, scrub, or strip the concrete using Ameripolish® Strip and Clean to remove any surface contamination or film. Product must be able to penetrate the surface without error.

### Product Specification

<b>Application:</b>	Spray and Scrub
<b>Appearance:</b>	Milky liquid
<b>VOC:</b>	Compliant (0g/l)
<b>Shelf life:</b>	1 year
<b>Solvent:</b>	Water-Based

### Packaging Specification

Product #	Shipping Wt.	Container
ECOMS-55	531 lbs.	55 gallons RTU
ECOMS-250	2,445 lbs.	250 gallons RTU



Category > Strengthen

## Eco-Hard MS

### Mono Silicate Densifier

Single application only. Apply with low-pressure sprayer (power), and spread evenly with Ameripolish® Microfiber Mop. Allow the surface to remain wet for at least 15 minutes. Wait 1 to 3 hours for product to dry. The surface may be used as soon as the application is complete and the surface is again dry to the touch. Newly laid surfaces require the normal hardening period.

### Cleanup

Ameripolish® Eco-Hard MS washes up quickly with soap and water.

### Storage

- Store upright in safe dry place at 40-105F° (4 -41C°)
- Keep product from freezing
- Keep out of reach of children
- Seal container after use
- Do not mix with other chemicals

### VOC Compliance

In addition, Ameripolish® Eco-Hard MS offers VOC compliance with low VOC at 0 g/L and is also compliant with national, state, and district regulations:

- US Environmental Protection Agency
- California Air Resources Board SCM Districts\*
- South Coast Air Quality Management District\*
- Maricopa County, AZ
- Northeast Ozone Transport Commission

\*Before application, verify product conformance with local and state codes.

### Warning & Safety Information

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE READ THE SAFETY DATA SHEET IN ITS ENTIRETY! Safety Data Sheets (SDS) can be found online at [www.ameripolish.com](http://www.ameripolish.com) or upon request by contacting Ameripolish at 1-800-592-9320.