

PREPARE ★ COLOR ★ STRENGTHEN ★ PROTECT ★ MAINTAIN

SURFACE PREPARATION

CONCRETE DYES

DENSIFIERS

SEALERS & STAIN PROTECTION

CLEANERS & MAINTENANCE PADS

## Ameripolish® EZ-Kut Grinding Agent



Ameripolish® EZ-Kut Grinding Agent is a water based, pretreatment, rapid surface preparation agent used for the initial cut on hard, dense concrete and helps with exposing large aggregate faster than dry only or standard wet methods. EZ-Kut also helps by dramatically increasing the productivity of lower-grit diamond tooling. EZ-Kut Grinding Agent achieves this by suspending concrete solids away from the surface for diamond tools to achieve maximum efficiency. This then shortens the project time-line, reduces labor costs and extends the life of diamond tooling. EZ-Kut is also unique in that it can be used in wet and dry grinding methods.



#### **Features**

- Speeds up the time spent on initial cut on hard, dense concrete
- Helps with exposing large aggregate faster than dry only or standard wet methods
- Maximizes efficiency, increases productivity and extends the life of diamond tooling
- Reduces labor costs
- Shortens the project time-line
- Unique DRY method avoiding the hassle of dealing with slurry



# **EZ-Kut Grinding Agent Details**

#### PRODUCT SPECIFICATIONS

Application	Sprayer or push broom
Appearance	Clear liquid
voc	Compliant (1g/l)
Shelf Life	2 years
Solvent	Water Based

Product #	Shipping Weight	Container(s)	Coverage sq.ft./G
EZKUT-1	10 lbs.	1 gallon - RTU	200 - 400
EZKUT-5	50 lbs.	5 gallons - RTU	1,000 - 2,000
EZKUT-30	300 lbs.	30 gallons - RTU	6,000 - 12,000
EZKUT-55	550 lbs.	55 gallons - RTU	11,000 - 22,000
EZKUT-250	2,500 lbs.	250 gallons RTU	50,000 - 100,000

#### **WARRANTY**

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.

### **CAUTION**

WARNING-Before using or handling this material, read the Material Safety Data Sheet and Warranty. EYE, SKIN AND GASTRO-INTESTINAL TRACT AND RESPIRATORY TRACT IRRITANT. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists generated by this product. Use appropriate eye protection, and chemical-resistant gloves. Material is not flammable, but if exposed to fire material may produce irritating vapors and toxic gases (e.g., carbon dioxides and peroxides). KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.



Ameripolish, Inc. 120 Commercial Ave. Lowell, AR 72745 USA www.ameripolish.com Toll Free: 1-800-592-9320 Office: +1 479-725-0033 Fax: +1 479-725-0031 E-Mail: info@ameripolish.com