



CC&L International TriSeel PLUS®, Page 1 of 2

PRODUCT FEATURES

DESCRIPTION

CC&L International TriSeel PLUS® is a low VOC (5g/L) solvent-borne, clear penetrating oil and water repellent. **CC&L International** TriSeel PLUS® penetrates epoxy and cementitious terrazzo without leaving topical residues. The chemical properties of **CC&L International** TriSeel PLUS® provide superior coverage at 5,000 square feet per gallon with excellent penetration. **CC&L International** TriSeel PLUS® is manufactured in the U.S.A.

PERFORMANCE

- Resists stains from oil and food substances
- For pedestrian, vehicular, and high traffic areas.
- Durable protection.
- High coverage rate.
- Typically no impact on substrate colors.
- Non-flammable.
- Long “window” of ‘opportunity’ for cleaning spills.

PREPARATION

When using a broom, dust mop or vacuum, remove loose grit and other materials from floor prior to using **CC&L International** TriSeel PLUS®.

WARNING: CC&L International TriSeel PLUS® is intended for use on industrial and commercial terrazzo type surfaces. Protect People, property, vehicles, animals, glass, plants, and any other surfaces other than those receiving **CC&L International** TriSeel PLUS® from splash, overspray, residue and wind-drift.

TEMPERATURE GUIDELINES

Use **CC&L International** TriSeel PLUS® with air and surface temperatures of 40-90°F (4-32°C). Do not apply **CC&L International** TriSeel PLUS® below or above these temperatures. Avoid application in high winds.

REGULATORY COMPLIANCE

TriSeel PLUS® is compliant with most local, state and national VOC regulations. Including the following:

- U.S. Environmental Protection Agency
- California Air Resources Board SCM Districts*
- South Coast Air Quality Management District*
- Maricopa County
- AZ NorthEast Ozone Transport Commission

*Always verify product conformance with local and state related codes prior to application.

APPLICATION

Read and fully understand all “Preparation” and “Safety Information”, prior to the application of **CC&L International** TriSeel PLUS®. Always test surfaces for desired results prior to commencing work.

Recommended method of application is with a low-pressure (40 psi or less) pump sprayer and a conical tip with a microfiber pad and applicator.

1. Apply **CC&L International** TriSeel PLUS®. In one continuous application. Apply enough product to keep surface wet for approximately 2 to 3 minutes.
2. Spread **CC&L International** TriSeel PLUS® with a microfiber pad and applicator. Allow time to dry. Do not allow **CC&L International** TriSeel PLUS® to pool or puddle.
3. If needed, burnish surface with a high speed machine and 3,000 grit or higher diamond-impregnated maintenance pad to remove any residue from surface.
4. On porous surfaces a second application may be required to provide optimum surface protective. Apply only after first coat is dry and burnished.

COVERAGE

TriSeel PLUS® is ready-to-use and should be diluted with any other material.

Typical coverage is,

- 4,000 to 6,500 square feet per U.S. gallon.
- 280 to 420 square meters per U.S. Gallon.

**PRODUCT FEATURES****DRYING TIME**

Light foot traffic may be allowed a minimum of one hour after CC&L International TriSeel PLUS® has dried. Surfaces should be protected from excessive moisture and vehicular traffic for a minimum of 8 hours after application. Resistance to oils and acids begins 24 hours after application and full resistance is typically achieved in seven days.

CLEAN-UP

Clean tools and equipment immediately with mineral spirits or equivalent cleaning solvent. Rundowns and spills should be removed immediately. Do not reuse containers.

STORAGE AND HANDLING

Store CC&L International TriSeel PLUS® in a cool dry area. Keep containers upright and tightly closed when not in use. Do not allow CC&L International TriSeel PLUS® to freeze. CC&L International TriSeel PLUS® should be discarded if freezing does occur. Product has approximate shelf life of 1 year with factory-sealed container stored under instructed conditions. Do not mix CC&L International TriSeel PLUS® with other chemicals. Maintain temperatures of 45-105° F (7-40° C). Dispose of unused product in accordance with local, state and federal regulations.

MAINTENANCE

Remove staining agents from treated areas as soon as possible. Many cleaners are destructive to terrazzo surfaces including those treated with CC&L International TriSeel PLUS®. Only use cleaners specifically formulated for CC&L International TriSeel PLUS® covered surfaces. CC&L International recommends that you continue to use CC&L International Clean Concentrate® and a TriSeel Clean & Shine Maintenance Pad as an ongoing daily cleaning solution.

SAFETY INFORMATION

Reference the Material Safety Data sheet prior to handling and applying TriSeel PLUS®. TriSeel PLUS® may be an irritant to the skin, eyes and respiratory system. Avoid contact with eyes, skin, and clothing. Breathing vapors or mists produced by this product should be avoided. Always use appropriate eye protection and chemical resistant apparel. Keep work area ventilated. Use safety equipment and other necessary controls during application and handling. TriSeel PLUS® is non-flammable and non-combustible. **KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.**

FIRSTAID***Ingestion:***

DO NOT induce vomiting. Contact physician or Poison Control Center immediately.

Eye Contact:

Immediately flush eyes for 15 minutes in clear running water; hold eyelids open. If irritation persists, seek medical attention.

Skin Contact:

Wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation:

Move to a fresh air area.

Skin Contact:

Wash affected area with soap and water. If irritation persists, seek medical attention.

WARRANTY

The information contained herein is based on laboratory testing and believed to be accurate. Due to an inability to anticipate all variations or possible applications CC&L International cannot guaranty the reliability of the information listed herein. The applicator is responsible to test and determine product suitability for each intended purpose. CC&L International warrants this product to be free of defects only, unless otherwise required by law. Since manufacturer does not exercise control of product's use or project conditions, CC&L International, represents and warrants only that this product is of consistent quality within manufacturing tolerances. **NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESS OR IMPLIED, IS AUTHORIZED OR WARRANTED BY CC&L International, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR THE EFFECTS OR RESULTS OF SUCH USE. CC&L International WILL NOT BE LIABLE FOR SPECIAL INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING DAMAGES FOR DELAYS OR LOST PROFITS.**

Claims must be made in writing and received within 90 days from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.