



PROSOCO  
SINCE 1939

**CONSOLIDECK®**  
HIGH PERFORMANCE CONCRETE

www.prosoco.com

# Oil & Grease STAIN REMOVER

*poultice cleaner for embedded oil & grease stains*

**Instant poultice cleaner draws embedded oil and grease stains out of stone, tile and concrete.**

- Restoration Cleaning
- Stain Removal
- New Construction Cleaning
- Maintenance Cleaning
- Surface Protection

**CAUTION**  
MAY CAUSE IRRITATION  
Read Full Label for Precautionary Instructions Before Use

FIVE GALLONS - 18.9 L

### Our Guarantee of Excellence

PROSOCO products are laboratory tested and field proven. We guarantee their effectiveness when applied correctly. For more specific application instructions, Product Data Sheets and Material Safety Data Sheets are available at [www.prosoco.com](http://www.prosoco.com) or by calling PROSOCO Customer Care at 1-800-255-4255.

#### PRODUCT FEATURES

- Works on old, deeply set stains.
- Easy to use. No mixing or scrubbing needed.
- Works on concrete.
- Leaves no residue.
- Removes motor oil, brake and power-steering fluids, anti-freeze, hydraulic fluids, cooking oils, food grease and other oil-based stains.
- Won't discolor concrete.

#### PREPARATION

**Protect** people, vehicles, plants, nearby property and non-masonry surfaces from contact with product. Test all surfaces that may come in contact for compatibility. Immediately rinse non-target materials with water.

#### Surface & Air Temps

Best air and surface temperatures for cleaning are 50°F (10°C) or above. If freezing conditions exist before application, let substrate thaw.

#### Equipment

Use broom or other stiff-bristled brush, and dustpan to sweep up dried poultice. Though not required, high-pressure air can be used to "blow-out" extremely porous surfaces after sweeping.

#### Storage & Handling

Store in a cool, dry place. Keep container tightly closed when not dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperatures of 45-100°F (7-38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

#### APPLICATION

**Before use, read "Preparation" and "Safety Information."** ALWAYS TEST each type of surface and each type of stain for suitability, dwell-time and results. Use the following application instructions.

#### Dilution

Use in concentrate. Do not dilute. Shake well before use.

#### Coverage Rates

- 1 Quart cleans approximately 6 sq.ft. (0.5 sq.m.)
- 1 Gallon cleans approximately 24 sq.ft. (2 sq.m.)

#### Application Instructions

1. Scrape debris and buildup from surface. Do not pre-wet.
2. Shake well. Pour onto the oil-stained surface until it completely covers the stain. The batter-thick poultice will automatically reach its required thickness as it spreads out across the stain.
3. Let the poultice dry for 5-8 hours or overnight. Protect from pedestrian traffic and rain during dwell period. Regarding rain protection, a plastic "tent" over the poultice will allow proper drying. Avoid using tightly-adhered plastic covers. Dry times may vary with environmental conditions such as temperature, wind and humidity. The poultice surface develops cracks as it contracts and dries. A fully developed network of cracks indicates the poultice is completely dry.
4. Sweep up the dry powder and dispose. On porous substrates, pressure water rinsing may facilitate removal of poultice dust.

Most oil and grease stains can be cleaned with one application. Severe, deeply-embedded stains may redevelop after cleaning, requiring further applications.

#### Cleanup

Brush-out brooms and wipe down dustpans with a damp cloth. High-pressure air may also be used to remove dust residues from brooms, brushes and dustpans.

#### SAFETY INFORMATION

**Contains** silica/surfactant blend. May be harmful if swallowed. Avoid eye and skin contact. Wear personal protective equipment as necessary to avoid contact. Avoid breathing dusts during removal. Wear a dust respirator as needed. Do not alter or use for purposes other than specified. Store in cool, dry place. Do not reuse container. Please procure a Material Safety Data Sheet and Product Data for additional use and cautionary information. Maximum VOC Content: 4% at dilution.

**Keep Out Of The Reach Of Children.**

#### FIRST AID

**Ingestion:** Do not induce vomiting. If conscious, give large amounts of water and call a physician, emergency room or poison control center immediately.

**Eye Contact:** Rinse thoroughly for 15 minutes. Get medical attention.

**Skin Contact:** Rinse thoroughly. Get medical attention if irritation persists.

**Inhalation:** Remove to fresh air. Get medical attention as necessary.

**24-Hr Emergency Information: INFOTRAC at 800-535-5053**

#### WARRANTY

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

#### CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care - technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at [www.prosoco.com](http://www.prosoco.com), for the name of the Consolideck® representative in your area.

LOT#

Shelf Life: 2 years in tightly sealed, unopened container.

# OIL & GREASE STAIN REMOVER

<b>H</b> HEALTH	<input type="checkbox"/>	<b>1</b>
<b>F</b> FLAMMABILITY	<input type="checkbox"/>	<b>0</b>
<b>R</b> REACTIVITY	<input type="checkbox"/>	<b>0</b>
PERSONAL PROTECTION	<input checked="" type="checkbox"/>	<b>X</b>



KEEP FROM FREEZING

LOT#


Shelf Life: 2 years in tightly sealed, unopened container.

# OIL & GREASE STAIN REMOVER

<b>H</b> HEALTH	<input type="checkbox"/>	<b>1</b>
<b>F</b> FLAMMABILITY	<input type="checkbox"/>	<b>0</b>
<b>R</b> REACTIVITY	<input type="checkbox"/>	<b>0</b>
PERSONAL PROTECTION	<input checked="" type="checkbox"/>	<b>X</b>




KEEP FROM FREEZING



PROSOCO  
 3741 Greenway Circle • Lawrence, KS 66046  
 1-800-255-4255 • www.prosoco.com

ORG: USA  
 MOD: 460087  
 DSC: Oil & Grease Stain Remover  
 SIZ: 5 gallons  
 QTY: 1 Each  
 Item# 46000 - CDOGSR  
 Label Updated - 01/10/08  
 ©Copyright PROSOCO, Inc., 2008



PROSOCO  
 3741 Greenway Circle • Lawrence, KS 66046  
 1-800-255-4255 • www.prosoco.com

ORG: USA  
 MOD: 460087  
 DSC: Oil & Grease Stain Remover  
 SIZ: 5 gallons  
 QTY: 1 Each  
 Item# 46000 - CDOGSR  
 Label Updated - 01/10/08  
 ©Copyright PROSOCO, Inc., 2008