




Husqvarna PG 680 RC

PG 680 RC is a remote-controlled concrete floor grinder with unique oscillation function and Dual Drive Technology™. Compared to standard floor grinders this remote-controlled grinder enables significantly higher productivity and even better work results together with more ergonomic operation and effortless transportation to and from the work site. It also frees you to prepare the next set of tools, adjust hoses etc while the machine is running, which means better use of your time. With a grinding width of 680 mm it easily passes through a standard door. It's suitable for industrial applications and an excellent choice for concrete floor preparation and repair as well as all polishing and grinding applications - both wet and dry. Perfect for HiPERFLOOR® concrete floor polishing system.



INCREASED PRODUCTIVITY WITH REMOTE CONTROL

Higher output as optimum grinding parameters can be maintained over time. More grinding hours per day since you can operate and prepare next steps simultaneously. For example you can apply GM 3000 with a broom at the same time as you run the machine.




UNIQUE FUNCTION FOR FLATTER FLOORS

Replication of manual grinding movements (oscillation), gives best possible grinding pattern by adjusting amplitude and frequency. Gives a flatter floor by eliminating so called ridges otherwise created between passes. At the same time, the oscillation function saves time for the operator, as you only have to go over the floor once with the machine, instead of using the cross



DUAL DRIVE TECHNOLOGY™

Dual Drive Technology™ - fully independent control of both planetary and satellite grinding heads in regards to speed and direction of rotation.



CONSISTENT OPTIMUM GRINDING PERFORMANCE

Parameter settings enables optimum grinding and polishing for each application. Consistent operation and result, even when changing operator.

Features Husqvarna PG 680 RC

- Accessible for most jobs.
- Ergonomic operation
- User-friendly remote control
- Effortless transportation
- High power machinery with Dual Drive Technology™ capable of delivering high production rates, increasing profit and saving valuable time.
- Easy transportation
- Drive wheels that work on difficult surfaces
- HCP, Construction, PG, Surface Prep
- Redi Lock® is an instant and hassle-free system for changing diamond tooling.
- Redi Lock® is an instant and hassle-free system for changing diamond tooling. Robust system design ensures maximum protection and life of your diamond tools.

TECHNICAL SPECIFICATION	
Power output	17.5 hp
Phases	3
Grinding width	27.5"
Grinding disc	9"
Grinding pressure total	593 lbs
Grinding disc speed	250-1100 rpm
Planetary head speed	5-65 rpm
Direction of rotation	Independent direction of rotation FWD/REV for grinding discs and planetary head.
Weight	1097 lbs
Vibrations left handle	1.36 m/s ²
Vibrations right handle	1.4 m/s ²

