



Husqvarna K 970

The new Husqvarna K 970 is our latest and most powerful handheld power cutter, featuring the revolutionary X-Torq® engine technology. It is a unique machine, in a class of its own when it comes to emission levels, efficiency and maneuverability.




LIGHT AND POWERFUL

A light, compact and powerful machine with superior power-to-weight ratio.



LONG SERVICE INTERVALS

A strong Poly-V belt combined with our maintenance-free starter DuraStarter™ and efficient filter-system Active Air Filtration™ ensures long service intervals.



ROBUST AND RELIABLE

Less sensitive to outer conditions and fuel variations, thanks to the cylinder design and muffler with integrated heat deflector.



EASY TO START

The unique design of the carburettor, cylinder and digital ignition system, together with air purge and decompression valve ensure an easy start.

Features Husqvarna K 970

- Less slurry and low water consumption
- Low fuel consumption and emissions
- Ergonomic and easy cutting
- Easy to change blade guard position
- High power with less fuel
- Fits multiple blade bushings
- Made for easy refuelling.
- Blade retarder
- The new generation of Active Air Filtration™ is one of the most efficient air filtration systems on the market.
- Patented, dust sealed starter unit with a sealed return spring and pulley bearing. DuraStarter™ also includes a starter cord with greatly increased durability. This makes the starter virtually maintenance free, further enhancing the reliability of our cutters.
- Our built-in automatic filter compensation maintains high power during the air filter life time.
- Easy to start thanks to Air Purge and decompression valve.

TECHNICAL SPECIFICATION	
Engine	Air-cooled 2 stroke engine
Cylinder displacement	5.71 cu.inch
Power output	6.5 hp
Fuel tank volume	33.8 fl oz
Idling speed	2700 rpm
Vibrations front handle	3.9/3.4 m/s ²
Vibrations rear handle	4.2/4.8 m/s ²
Sound pressure level at operators ear	104 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Blade diameter	14/16 "
Max cutting depth	5/6 "
Combined bushing diameter	0.79/1 "
Weight (excl. cutting equipment)	24/26.2 lbs
Fuel tank volume	2.1 US pint

