

RSEV 19-125 RT (603825750) Renovation grinders Plastic Carry Case

Order no. 603825750
EAN 4007430313669



Representative picture



- For effective spot sanding and removal of concrete, screed and coatings with diamond cup wheels
- High torque and overload capacity for demanding applications in continuous use
- Low weight, ideal for sanding walls and ceilings
- Working close to edges thanks to integrated folding segment
- Optimum extraction results: Spring-mounted brush rim at the protective cover that adapts to any surface and segment height
- Front handle for safe and uniform guidance when polishing, adjustable without the need for tools
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly.

Technical values

Parameters

Amps	15 AMPS
Grinding wheel Ø	5 "
Torque	44 in-lbs
No-load speed	3800 - 8200 RPM
Rated input power	1900 W
Output power	1240 W
Revolutions at rated load	6800 RPM
Spindle thread	5/8" - 11 UNC
Weight (without power cable)	7.7 lbs
Cable length	8 ft

Vibration

Surface grinding	6.94 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	92 dB(A)
Sound power level (LWA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Bow type handle
 Inner support flange
 Nut with two holes
 Plastic carrying case
 Replacement sealing brush
 Suction adapter
 Spanner wrench