

**SAFETY DATA SHEET**

Metzger / McGuire Co. Polyurethane Prepolymer

**1. Identification**

**1.1 Product Name: Rapid Refloor XP Part B ISO**

**1.2 Recommended Use:** Component of a Control Joint Polyurethane System. Caulking and sealing.

**Issue Date:** 3/27/15

**Supersedes:** 1/30/15

**Reason for revision:** Update Hazards Classification.

**1.3 Manufacturer:**

Metzger/McGuire Co.  
PO BOX 2217  
CONCORD, NH 03302-2217  
PH: (800) 223-6680  
FAX: (603) 224-6020  
Email: info@metzgermcguire.com

**1.4 In Case of Emergency: INFOTRAC: 1-800-535-5053**

Outside the US and Canada, call 1-352-323-3500

**2. Hazards Identification**

**2.1 OSHA/HCS status: This material is considered hazardous under OSHA Hazard Communication Standard (29 CFR 1910.1200).**

According to EC No. 1272/2008 (CLP/GHS): Xi, Skin and respiratory irritant. Respiratory sensitizer.

**Classification: Acute Toxicity: Inhalation - Cat. 4**

**Skin corrosion/irritation - Cat. 2**

**Serious Eye Damage/ Eye irritation - Cat. 2A**

**Respiratory Sensitization - Cat. 1**

**Skin Sensitization - Cat. 1**

**Specific Target Organ Toxicity (single exposure)**

**[respiratory tract irritation] - Cat 3**

**2.2 GHS Label Elements:**

**Hazard pictograms:**

**Signal word:**



**Warning**

**Danger**

**2.3 Hazard statements:**

H315 Causes skin irritation.

# SAFETY DATA SHEET

Metzger / McGuire Co.

Polyurethane Prepolymer

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

## 2.4 Precautionary statements:

P261 Avoid breathing vapor.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the work place.

P273 Avoid release to the environment.

P281 Wear protective gloves / protective clothing / eye protection / face protection.

P302 + P352 **IF ON SKIN:** Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice / attention.

**GENERAL INFORMATION:** Read the entire SDS for a more thorough evaluation of the hazards.

## 3. Composition/Information

	<u>Name</u>	<u>CAS number</u>
3.1 Substances	4,4'-Diphenylmethane Diisocyanate	101-68-8
3.2 Mixture:	Concentration of composition has been withheld as a Trade Secret	

## 4. First Aid Measures

**4.1 Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with plenty of running tepid water for 15 minutes, occasionally lifting the upper and lower eyelids. If effects occur get medical attention immediately.

**Skin contact:** Wash immediately with warm soapy water. Corn oil may be more effective than soap and water. Get medical attention if irritation develops. Wash clothing before re-use. Discard personal items that cannot be decontaminated.

**Inhalation:** Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately. Loosen clothing such as collar, tie, belt or waistband.

**Ingestion:** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Notes to Physician:** No specific treatment. Treat symptomatically. Call poison control center if large quantities have been ingested.

## 4.2 Symptoms of exposure:

**Eye contact:** Irritation, watering, redness and pain.

**Skin contact:** Irritation, redness, itching.

**Inhalation:** Dizziness, difficulty breathing if fumes are highly concentrated.

**Ingestion:** No specific data, may cause irritation.

## 5. Fire-Fighting Measures

**NFPA Flammable classification:** Combustible liquid III B

**Flash point:** >110°C (Setaflash)

### 5.1 Extinguishing Media

# SAFETY DATA SHEET

Metzger/McGuire Co.

Polyurethane Prepolymer

**Suitable:** Carbon dioxide, foam, dry chemical.

**Not Suitable:** Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous.

**5.2 Special hazards:** Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In a fire or if heated, pressure will increase in containers which may burst.

**5.3 Special protective actions for fire fighters:** Use protective fire fighting clothing and positive pressure self-contained breathing apparatus (SCBA) to protect against potential harmful and/or irritating fumes. Do not use high volume water jet as this may spread the area of the fire.

## 6. Accidental Release Measures

**6.1 Personal precautions:** Isolate area; keep unnecessary and unprotected personnel away from spill area. Avoid contact with skin, eyes and clothing. Use appropriate safety equipment. No health effects expected from the cleanup of this material if contact can be avoided. Provide adequate ventilation.

**6.2 Environmental precautions:** Avoid disposal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**6.3 Methods for cleaning up:** Contain and absorb large spills with an inert, non-flammable absorbent carrier (such as earth, sand or clay). Shovel or pump into labeled open-top drums or plastic bags for further decontamination if necessary. Apply lids loosely to avoid pressure build-up. Wash the spillage area clean with a mixture of water and non-ionic surfactant or a suitable liquid detergent. (See section 13 for disposal considerations). Notify applicable government authorities if release is reportable. CERCLA RQ for 4,4-MDI is 5,000 lbs.

## 7. Handling and Storage

**7.1 Precautions for safe handling:** Avoid personal contact with the product. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded. Regularly monitor the efficiency of the ventilation system. Avoid breathing aerosols, mists and vapors. (See section 8 Exposure control for details). Keep stocks of de-contaminant readily available.

**7.2 Storage:** Keep containers tightly closed and store in a cool, dry well ventilated area at 68-86F.

## 8. Exposure controls/personal protection

**8.1 Exposure parameters:** Diphenylmethane 4,4'-diisocyanate:

ACGIH TLV (TWA): 0.005 ppm 8 hrs. Ceiling Limit Value: 0.02 ppm CEIL: 0.2 mg/m<sup>3</sup>

**8.2 Engineering controls:** Ventilation through local exhaust if appropriate.

**Eye/face protection:** Safety glasses, goggles, face mask as appropriate.

**Skin & hand protection:** Protective clothing as necessary to guard against product contact. PVC, neoprene or nitrile rubber gloves, safety shoes.

**Respiratory protection:** Not needed under normal use conditions under adequate ventilation.

**Other protective equipment:** Eye wash stations and emergency showers should be available. The type and degree of personal protective equipment will depend on the specific work operation.

**8.3 Environmental exposure controls:** See Exposure parameters.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties.

<b>Appearance</b>	: Liquid
<b>Color</b>	: Clear, pale yellow
<b>Type of odor</b>	: Slight aromatic
<b>Vapor pressure</b>	: < 0.0001 mmHg kPa @ 25°C
<b>Flash Point</b>	: >200°C (Pensky-Martens Closed Cup)

# SAFETY DATA SHEET

Metzger / McGuire Co.

Polyurethane Prepolymer

Boiling point	: >200°C @ 5 mmHg
Freezing Point	: 5-20°C (41-68°F)
Specific gravity	: 1.2 grams / cc
Water solubility	: Insoluble, reacts slowly with water to liberate CO <sub>2</sub> gas.

## 10. Stability and Reactivity

**10.1 Reactivity:** Reacts with water producing carbon dioxide gas. Exothermic reaction with materials containing active hydrogen groups.

**10.2 Stability:** Stable at room temperature.

**10.3 Hazardous polymerization:** May occur under certain conditions of storage and use..

**10.4 Conditions to avoid:** Water, alcohol, amines, strong bases and acids.

**10.5 Incompatible materials:** Water, alcohols, amines, bases and acids.

**10.6 Hazardous decomposition products:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN.

## 11. Toxicological Information

**11.1 Acute Inhalation Toxicity:** LC50: >490 mg/m<sup>3</sup>, 4 h (rat)

**11.2 Acute Oral Toxicity:** LD50 >2,000 mg/kg (rat, Male/Female)

**11.3 Acute Dermal Toxicity:** LD50 >10,000 mg/kg (rabbit)

**11.4 Skin and Eye Irritation:** Slightly irritating (rabbit)

## 12. Ecological Information

**12.1 Acute and Prolonged Toxicity to Fish:** LC0: >1,000 mg/l (zebra fish, 96h)

**12.2 Persistence and degradability:** Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

## 13. Disposal Considerations

**13.1 Waste treatment methods:** Do not dump into any sewers, on the ground, or into any body of water. Significant quantities of waste product residues should be processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local requirements.

**Container disposal:** Drain container of all residual material prior to disposal.

## 14. Transport Information:

**14.1 Land transport (DOT):** Not regulated in single containers of less than 5,000 lbs.

**14.2 Proper Shipping name:** Other regulated substances, liquid, n.o.s.  
(contains 4,4' - Diphenylmethane Diisocyanate (MDI))

**14.3 Hazard Division/Label:** Class 9 UN/NA Number: NA3082 PG III

**14.4 Reportable Quantity:** 5,000 lbs. Single containers less than 5,000 lbs. are not regulated.

**14.5 Sea transport (IMDG)** Not regulated

**14.6 Air transport (ICAO/IATA)** Not regulated

## 15. Regulatory Information

**15.1 Unites States Safety Health and Environmental Federal regulations/legislation:**

## SAFETY DATA SHEET

Metzger/McGuire Co.

Polyurethane Prepolymer

OSHA Hazcom Standard Rating: Hazardous.

SARA Title III Section 302 (40CFR355, Appendix A): Extremely Hazardous Substance. None.

SARA Section 311/312 Hazard Categories: Acute Health Hazard, Chronic Health Hazard.

SARA RTK Title III Section 313 (EPCRA) (40CFR 372.65) Contains 4,4 Diphenylmethane Diisocyanate (MDI)

CERCLA Hazardous Substances (40CFR302): 4,4-Diphenylmethane Diisocyanate (MDI) RQ: 5,000 lbs.

TSCA Inventory status: Listed.

Canadian CEPA DSL Status: All components are listed or exempted..

Canadian WHMIS Classification: Class D-2A Material causing other toxic effects (very toxic).

Class D-2B Material causing other toxic effects (toxic)

OSHA/NTP/IARC Carcinogen Status: Not listed.

Chemicals known to the state of California (Prop 65) to cause cancer or reproductive toxicity: None

Pennsylvania (Worker and Community Right-to-Know Act): Diphenylmethane 4,4'-diisocyanate.

### 16. Other Information

**HMIS/NFPA rating:** Health: 2\* Fire: 1 Reactivity: 1 Personal Protection: H

**Label requirements:** Harmful by inhalation. Irritating to the eyes, skin and respiratory system. May cause sensitization by inhalation and skin contact. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitized persons. (Personal protective equipment selection is best assigned by the user after performing a hazard assessment on the product as it is to be used in the specific work process). \* = Chronic health hazard