



CREATING A CLEANER, SAFER, HEALTHIER WORLD.

EQUIPMENT



T600e

WALK-BEHIND FLOOR SCRUBBER

Delivering exceptional cleaning performance, durability and dependability day in and day out.

CLEANING PERFORMANCE YOU CAN COUNT ON WITH HEAVY-DUTY CONSTRUCTION AND A SUITE OF PRODUCTIVITY-BOOSTING FEATURES



- **Scrub longer between empty and fill cycles** with large-capacity solution and recovery tanks.
- **Clean virtually any hard floor surface** with a wide range of cleaning heads, including an orbital option.
- **Maximize battery life and run-time** with the optional Smart-Fill™ automatic battery watering system.
- **Help prevent breakdowns and simplify preventative maintenance** with easy-to-identify yellow maintenance touch points.
- **Simplify operation and training** with easy-to-understand controls featuring variable speed control bail, propel toggle and speed setting within easy reach.
- **Withstand the toughest environments** with industrial grade construction featuring corrosion-resistant scrub deck and rust-proof polyethylene body and tanks.

INNOVATIVE, EXCLUSIVE TECHNOLOGIES

SMART-FILL™ AUTOMATIC BATTERY WATERING

Smart-Fill™ makes battery maintenance safer by removing the task of checking, opening, and filling flooded batteries.



ec-H2O NanoClean® technology electrically converts water into an innovative cleaning solution that cleans effectively, saves money, improves safety, and reduces environmental impact compared to daily cleaning floor chemicals and methods.†



Increase productivity, reduce cost to clean and make informed decisions with intelligent insights from IRIS® Asset Manager.

†ec-H2O NanoClean® technology is not suitable for all soils, including heavy concentrations of fats and oils. Depending on the type of soil, conventional chemical cleaners may be required.

INSIDE THE T600e



Orbital Scrubbing is ideal for daily scrubbing, cleaning grouted tile or chemical-free floor finish removal.

Help floors battered by grime and filth look like new with TennantTrue® Stone Care Solutions.

Optimize equipment performance and protect your investment with TennantTrue® parts and service.

AVAILABLE FEATURES



T600e WALK-BEHIND FLOOR SCRUBBER

	DUAL DISK			CYLINDRICAL		ORBITAL
	700 MM	800 MM	900 MM	700 MM	800 MM	700 MM
SCRUBBING SYSTEM						
Productivity (per hour) Theoretical Max	36,960 ft ² /hr 3,434 m ² /hr	42,240 ft ² /hr 3,924 m ² /hr	47,520 ft ² /hr 4,415 m ² /hr	36,960 ft ² /hr 3,434 m ² /hr	42,240 ft ² /hr 3,924 m ² /hr	36,960 ft ² /hr 3,434 m ² /hr
Estimated Coverage* – Conventional	24,005 ft ² /hr 2,230 m ² /hr	27,698 ft ² /hr 2,573 m ² /hr	31,391 ft ² /hr 2,916 m ² /hr	24,005 ft ² /hr 2,230 m ² /hr	27,698 ft ² /hr 2,573 m ² /hr	24,005 ft ² /hr 2,230 m ² /hr
Estimated Coverage* – ec-H2O NanoClean®	28,863 ft ² /hr 2,681 m ² /hr	33,304 ft ² /hr 3,094 m ² /hr	34,964 ft ² /hr 3,248 m ² /hr	28,863 ft ² /hr 2,681 m ² /hr	33,304 ft ² /hr 3,094 m ² /hr	28,863 ft ² /hr 2,681 m ² /hr
BRUSH DRIVE SYSTEM						
Scrub motor	2 x 36 VDC, .75 hp / .56 kW	2 x 36 VDC, .75 hp / .56 kW	2 x 36 VDC, .75 hp / .56 kW	2 x 36 VDC, .9 hp / .67 kW	2 x 36 VDC, .9 hp / .67 kW	1 x 36 VDC, .75 hp / .56 kW
Brush Pad RPM	200 rpm	200 rpm	200 rpm	760 rpm	760 rpm	2,200 rpm
Brush down pressure	Low: 150 lbs / 68 kg High: 200 lbs / 90 kg Heavy Duty (optional):	150 lbs / 68 kg 200 lbs / 90 kg 300 lbs / 136 kg	150 lbs / 68 kg 200 lbs / 90 kg	50 lbs / 23 kg 90 lbs / 41 kg	50 lbs / 23 kg 90 lbs / 41 kg	105 lbs / 48 kg 170 lbs / 77 kg
SOLUTION/RECOVERY SYSTEM						
Solution tank capacity	32 gal / 121 L	32 gal / 121 L	32 gal / 121 L	32 gal / 121 L	32 gal / 121 L	32 gal / 121 L
Recovery tank capacity	37 gal / 140 L	37 gal / 140 L	37 gal / 140 L	37 gal / 140 L	37 gal / 140 L	37 gal / 140 L
Vacuum motor	36 VDC, 0.75 hp .56 kW, 15.6 A	36 VDC, 0.75 hp .56 kW, 15.6 A	36 VDC, 0.75 hp .56 kW, 15.6 A	36 VDC, 0.75 hp .56 kW, 15.6 A	36 VDC, 0.75 hp .56 kW, 15.6 A	36 VDC, 0.75 hp .56 kW, 15.6 A
Vacuum water lift	50 in / 1,270 mm	50 in / 1,270 mm	50 in / 1,270 mm	50 in / 1,270 mm	50 in / 1,270 mm	50 in / 1,270 mm
CLEANING TECHNOLOGY						
Conventional	Standard	Standard	Standard	Standard	Standard	Standard
ec-H2O NanoClean®	Optional	Optional	Optional	Optional	Optional	Optional
BATTERY SYSTEM						
System Voltage	36 volt	36 volt	36 volt	36 volt	36 volt	36 volt
Battery Types						
Wet 240AH–6 required	Standard	Standard	Standard	Standard	Standard	Standard
Wet 360AH–6 required	Optional	Optional	Optional	Optional	Optional	Optional
Sealed 186AH Thin Plate Pure Lead–3 required	Optional	Optional	Optional	Optional	Optional	Optional
Battery run time Wet 360AH (up-to hours)**	5.1	5.0	5.0	6.4	5.8	6.1
Smart-Fill™ Automatic Battery Watering Tank Capacity (Option)	1.1 gal / 4 L	1.1 gal / 4 L	1.1 gal / 4 L	1.1 gal / 4 L	1.1 gal / 4 L	1.1 gal / 4 L
PROPELLING SYSTEM						
Scrubbing speed	3.0 mph / 4.8 kph	3.0 mph / 4.8 kph	3.0 mph / 4.8 kph	3.0 mph / 4.8 kph	3.0 mph / 4.8 kph	3.0 mph / 4.8 kph
Transport speed	3.3 mph / 5.3 kph	3.3 mph / 5.3 kph	3.3 mph / 5.3 kph	3.3 mph / 5.3 kph	3.3 mph / 5.3 kph	3.3 mph / 5.3 kph
MACHINE SPECIFICATIONS						
Length	63.7 in / 1,617 mm	65.8 in / 1,671 mm	69.3 in / 1,761 mm	64.4 in / 1,637 mm	64 in / 1,625 mm	62.6 in / 1,590 mm
Width	30.1 in / 764 mm	33.7 in / 856 mm	37.6 in / 955 mm	31.2 in / 792 mm	35.1 in / 892 mm	29.4 in / 746 mm
Height	43.6 in / 1,107 mm	43.6 in / 1,107 mm	43.6 in / 1,107 mm	43.6 in / 1,107 mm	43.6 in / 1,107 mm	43.6 in / 1,107 mm
Squeegee width	38.3 in / 973 mm	41.3 in / 1,049 mm	46.6 in / 1,234 mm	38.3 in / 973 mm	41.3 in / 1,049 mm	38.3 in / 973 mm
Aisle turnaround width	65 in / 1,650 mm	67 in / 1,700 mm	70 in / 1,775 mm	67 in / 1,700 mm	67.5 in / 1,713 mm	60.6 in / 1,540 mm
Weight (with heaviest batteries)	1,033 lb / 470 kg	1,036 lb / 471 kg	1,040 lb / 473 kg	1,049 lb / 477 kg	1,052 lb / 478 kg	1,059 lb / 481 kg
GVW	1,301 lb / 591 kg	1,304 lb / 593 kg	1,308 lb / 595 kg	1,317 lb / 599 kg	1,320 lb / 600 kg	1,327 lb / 603 kg
Sound level (operator's ear)***	69.5 dBA	69.5 dBA	69.5 dBA	69.2 dBA	69.2 dBA	69.5 dBA
T600e**** – APPROVALS (U.S./CANADA ONLY)						
ETL Listed to UL 583 Type E						
WARRANTY						
See your local representative for warranty information						
*Estimated coverage rates use the practical speed and empty/fill time standards from the 2014 ISSA 612 Cleaning Times & Tasks handbook.						
**Up to run-times are based on continuous scrubbing run-times, 360AH batteries, low down pressure, ec-H2O off.						
***Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment manufacturers & OSHA.						
****Does not include - ec-H2O NanoClean or Smart-Fill options.						
Specifications subject to change without notice.						



ec-H2O NanoClean® technology is NFSI (National Floor Safety Institute) Certified



ec-H2O NanoClean technology is registered by NSF International

SEEING IS BELIEVING

For a demonstration or additional information,
call +1.800.553.8033 or email info@tenantco.com

Tennant
701 North Lilac Drive
Minneapolis, MN 55422 USA

USA/Canada: +1.800.553.8033
Quebec: +1.800.361.9050
Overseas: +1.763.540.1315