



A product brand of LATICRETE International, Inc.



Sparta-Guard™

solid-color coatings

System Features & Benefits:

- 1-Day installation
- Next-day return to service
- UV stable
- Varied traction available
- All-climate application
- Superior substrate adhesion
- High-abrasion & chemical resistance
- Green-friendly options

Superior resistance to punishing industrial traffic, skydrol and other harsh chemicals. Popular where cleanliness is a must. A logical choice for demanding environments such as aviation hangars, manufacturing and shop floors.



System Variations	Overall Thickness	Applications
Sparta-Guard	9 mils DFT	Shop floors, industrial floors & other heavy-traffic applications
Sparta-Guard PURE	20 mils DFT	Minimal odor, VOC-free & interior applications

Coverage & Material Usage Guide

Sparta-Guard

Layer	Code	Description	Coverage
Prime Coat	115	Sparta-Flex Pigment Base Kit	330 sq ft/gal
	160-173	Reactint Pigment Pack	660 sq ft/qt
Second Coat	115	Sparta-Flex Pigment Base Kit	330 sq ft/gal
	160-173	Reactint Pigment Pack	660 sq ft/qt
Top Coat	100	Sparta-Flex Clear	330 sq ft/gal
	350-352	Sparta-Grip Traction Additive	3 oz/gal

Sparta-Guard PURE

Layer	Code	Description	Coverage
Prime Coat	150	Sparta-Flex PURE Pigment Base Kit	200 sq ft/gal
	160-173	Reactint Pigment Pack	400 sq ft/qt
Second Coat	150	Sparta-Flex PURE Pigment Base Kit	200 sq ft/gal
	160-173	Reactint Pigment Pack	400 sq ft/qt
Top Coat	140	Sparta-Flex PURE Clear	200 sq ft/gal

Note: Top Coat is Optional



Recommended Surface Preparation: CSP 2-3, grind or shot blast, just no acid etching.

Recommended Maintenance: Regular floor washing, depending upon floor traffic, with a pH neutral cleaner. Simple Green diluted with water works well.