



A product brand of LATICRETE International, Inc.



Sparta-Quartz™

quartz flooring

System Features & Benefits:

- High traction coefficients
- Interior or exterior use
- Superior durability & impact resistance
- Rapid return to service
- Cold-temperature cure
- Customizable quartz blends
- 3x more durable than epoxy
- High impact resistance

Highly-durable colored quartz aggregates are layered between Sparta-Flex coatings to create an attractively textured floor. Ideal for parking decks, stadiums and commercial kitchens.



System Variations	Overall Thickness	Applications
Sparta-Quartz	50 mils DFT	Interior or exterior heavy-traffic applications requiring high traction
Sparta-Quartz PURE	60 mils DFT	Minimal odor, VOC-free & interior applications

Coverage & Material Usage Guide

Sparta-Quartz	Layer	Code	Description	Coverage
	Prime Coat	115	Sparta-Flex Pigment Base Kit	330 sq ft/gal
		160-173	Reactint Pigment Pack	660 sq ft/qt
	Quartz Broadcast	323-338	Blended Quartz Aggregate (50 lb bag)	250 sq ft/bag
	Broadcast Coat	100	Sparta-Flex Clear	160 sq ft/gal
	Quartz Broadcast	323-338	Blended Quartz Aggregate (50 lb bag)	250 sq ft/bag
Grout Coat	100	Sparta-Flex Clear	160 sq ft/gal	
Top Coat	100	Sparta-Flex Clear	160 sq ft/gal	

Sparta-Quartz PURE	Layer	Code	Description	Coverage
	Prime Coat	150	Sparta-Flex PURE Pigment Base Kit	200 sq ft/gal
		160-173	Reactint Pigment Pack	400 sq ft/qt
	Quartz Broadcast	323-338	Blended Quartz Aggregate (50 lb bag)	250 sq ft/bag
	Broadcast Coat	150	Sparta-Flex PURE Clear	150 sq ft/gal
	Quartz Broadcast	323-338	Blended Quartz Aggregate (50 lb bag)	250 sq ft/bag
Grout Coat	150	Sparta-Flex PURE Clear	150 sq ft/gal	
Top Coat	150	Sparta-Flex PURE Clear	200 sq ft/gal	



Recommended Surface Preparation: CSP 2-3, grind or shot blast, just no acid etching.

Recommended Maintenance: Regular floor washing, depending upon floor traffic, with a pH neutral cleaner. Simple Green diluted with water works well.