



Enviro Klean®

NEXT GENERATION CLEANERS

DriKlean

Enviro Klean® DriKlean is a unique cleaning compound designed for interior cleaning where traditional liquid cleaners cannot be used safely or where rinsing may be impractical. DriKlean can be sprayed, rolled, or brushed onto the surface. The cleaner and soiling is then easily peeled off after drying. DriKlean removes dust, soot, oils and other surface soiling.

Gentle, yet powerful, Enviro Klean® DriKlean is safe for sensitive surfaces including limestone, sandstone, marble, travertine, plaster and terra cotta as well as traditional masonry such as concrete, mortar and brick.

ADVANTAGES

- Safe for use on sensitive surfaces.
- Easily peels off treated surfaces when dry.
- Low toxicity. Low odor.
- Increased viscosity for single coat application to most surfaces.
- Ready-to-use. Easy application by spray, brush or roller.
- Requires no rinsing or scrubbing.
- Contains no natural rubber latex.
- Contains up to 29% recycled material.

Limitations

- Not recommended for wood furniture or other finely finished wood surfaces.
- Not for use on gilded or other vulnerable surface finishes.
- Product efficiency is reduced when temperatures are below 40° F (4° C) or above 90° F (32° C).

REGULATORY COMPLIANCE

VOC Compliance

Enviro Klean® DriKlean is compliant with all national, state and district VOC regulations.

TYPICAL TECHNICAL DATA

FORM	Viscous white liquid
SPECIFIC GRAVITY	0.99
pH	9.8
WT/GAL	8.27 lbs
ACTIVE CONTENT	not applicable
TOTAL SOLIDS	not applicable
VOC CONTENT	<0.5%
FLASH POINT	>212° F (>100° C) ASTM D 3278
FREEZE POINT	32° F (0° C)
SHELF LIFE	1 year in tightly sealed, unopened container

SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application and handling.

24-Hour Emergency Information:
INFOTRAC at 800-535-5053

Product Data Sheet

Enviro Klean® DriKlean

PREPARATION

Protect people, property, sensitive materials, plants and all surfaces not set for cleaning from product, splash, residue, and fumes. Protect with polyethylene sheeting secured by masking or duct tape.

Best results are obtained when applied to dry surfaces. DriKlean may be applied to damp surfaces but should not be applied to wet surfaces, surfaces with standing water, or surfaces saturated with water.

Surface and Air Temperatures

Temperatures for application should be at least 40° F (4° C) and rising, and below 90° F (32° C).

Equipment

Mix DriKlean thoroughly with a low-speed drill and clean mixing paddle.

When roller applying, use a 3/4 inch (19 mm) nap roller.

Recommended for these substrates. Always test. Coverage is in sq.ft./m. per gallon.			
Substrate	Type	Use?	Coverage
Architectural Concrete Block	Burnished	yes	12–50 sq.ft. 1–5 sq.m.
	Smooth	yes	
	Split-faced	yes	
	Ribbed	yes	
Concrete	Brick	yes	12–50 sq.ft. 1–5 sq.m.
	Tile	yes	
	Precast Panels	yes	
	Pavers	yes	
	Cast-in-place	yes	
Fired Clay	Brick	yes	12–50 sq.ft. 1–5 sq.m.
	Tile	yes	
	Terra Cotta (unglazed)	yes	
	Pavers	yes	
Marble, Travertine, Limestone	Polished	yes	50–100 sq.ft. 5–9 sq.m.
	Unpolished	yes	12–100 sq.ft. 1–9 sq.m.
Granite	Polished	yes	50–100 sq.ft. 5–9 sq.m.
	Unpolished	yes	12–100 sq.ft. 1–9 sq.m.
Sandstone	Unpolished	yes	12–100 sq.ft. 1–9 sq.m.
Slate	Unpolished	yes	12–100 sq.ft. 1–9 sq.m.
Always test to ensure desired results. Coverage estimates depend on surface texture and porosity.			

When applying by brush, any brush for use with water-based acrylic paints is appropriate.

DriKlean may be sprayed using airless spray equipment fitted with chemical resistant fittings and a minimum tip size of 0.027–0.031 inches. Adjust air pressure to produce an even, full spray pattern. Airless sprayers that meet or exceed the following specifications are appropriate:

Tip Size: 0.027–0.031 inches

Fan Size: 8–12 inches

Pressure: 3000 psi

Flow Rate: 1.0–2.0 gal/min

Hose length (max): 100 ft

Motor: 5/8 hp

Remove all filters in sprayer and gun.

For spray applications, DriKlean may be diluted with up to 10% fresh water, or a 9 parts cleaner to 1 part water ratio. For example, up to 2 quarts of fresh water can be mixed with an unopened 5-gallon container. Always add fresh water to cleaner when mixing. Always test before proceeding with overall application.

CAUTION needs to be taken to prevent material from skinning during application to avoid partially dried material from being drawn into the spray pump equipment and causing excessive tip plugging.

Storage and Handling

Store in a cool, dry place. Keep from freezing. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperatures of 45–100°F (7–38°C). Do not double stack pallets. Dispose of in accordance with local, state and federal regulations.

APPLICATION

Read “Preparation” and the Safety Data Sheet before use.

ALWAYS TEST a small area (1 foot x 1 foot) of each surface to confirm suitability, coverage rate and desired results before beginning overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let surface dry thoroughly before inspection.

Product Data Sheet

Enviro Klean® DriKlean

Dilution & Mixing

Do not alter or use for purposes other than specified. Use in concentrate for most applications.

Stir or mix well before use with a low-speed drill and clean mixing paddle.

For spray applications, DriKlean may be diluted with up to 10% fresh water, or a 9 parts cleaner to 1 part water ratio. For example, up to 2 quarts of fresh water can be mixed with an unopened 5-gallon container. Always add fresh water to cleaner when mixing. Always test before proceeding with overall application.

Application Instructions

1. Mask off areas not to be cleaned with polyethylene film.
2. Work in sections no larger than 10 ft x 10 ft (3 m x 3 m) and apply masking tape to at least one leading edge to facilitate easier removal.
3. Apply DriKlean in a heavy coat of approximately 40–60 mils wet. Apply the coating over the edges of the polyethylene film or masking for a good seal around edges of area being cleaned and to facilitate removal.

NOTE: Extremely porous masonry or masonry with a rough texture may need two coats to ensure ease in peeling. Always test for peelability prior to attempting overall application.

4. Allow to dry completely. DriKlean typically dries and is ready to peel in approximately 12 to 18 hours but may take up to 24 hours depending on film thickness, temperature and humidity. Film is dry when it becomes translucent.
5. Starting at one edge pull the dried film from the substrate surface and dispose in accordance with local, state and federal regulations.

Cleanup

Clean tools and equipment with soap and water. Dried material may simply be peeled off.

BEST PRACTICES

Mix product thoroughly prior to application with a low-speed drill and clean mixing paddle.

Apply the coating over the edges of the polyethylene film or masking for a good seal and to facilitate removal.

Allow DriKlean to dry fully (at least 12–18 hours) prior to removal. Up to 24 hours may be required when thick films are applied or under cool, damp conditions. Do not allow the coating to remain on surface longer than 3 days prior to removal.

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support. Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, for the name of the PROSOCO representative in your area.

Porous masonry or masonry with a rough texture may need two coats to ensure ease in peeling. Always test peelability prior to attempting overall application.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care, toll-free, at 800-255-4255.