

5 GAL ratio 4A-1B

GROUT/METALLIC

3 GAL ratio 2A-1B

KEY #514-UV



FINISH

5 GAL

ratio

1A-4B



467HS

PRIMER



502

BINDER



510

1000 SQ FT P/KIT SOLID COLORS

2ND BROADCAST

CAN ADD PIGMENT

NOT CHEMICAL RESISTANT

NOT UV STABLE

GREAT FOR PATCH WORK

GREAT FOR SLOPE WORK

500 sq. ft. p/kit

150 sq. ft. p/gal using as a grout 250-300 sq. ft. p/gal over smooth surface

511

1000 SQ FT P/KIT SOLID COLORS

511 & 514

2ND BROADCAST

511-UV PART A

CAN ADD PIGMENT

CHEMICAL RESISTANT

UV STABLE (1 UV INHIBITOR)

GREAT FOR GROUTING

514

100% SOLIDS

MORE BREATHABLE

GLOSSY FINISH

• UV STABLE (2 UV INHIBITORS)

150 sq. ft p/kit metallic

150-200 sq. ft. p/gal using as a grout 250-300 sq. ft p/gal over smooth surface MUST USE QUARTZ SANDS

510-CV 510-CV

VERTICAL RESIN

510-CV

MIX W/QUARTZ OR SILCA SAND

• GROUT WITH 511

TOPCOAT WITH 467HS

NOT UV STABLE

40-60 lineal ft. p/kit

100% SOLIDS

LONGER WORKING TIME

LAST LONGER/DURABLE

GLOSSY FINISH

UV STABLE

2500 sq. ft. p/kit

500 sq. ft. p/gal



3-5 SURFACE PROFILE

- CAN ADD PIGMENT
- NOT CHEMICAL RESISTANT
- NOT UV STABLE

700-900 sq. ft. p/ kit

200-250 sq. ft. p/gal